

Specification Sheet



Specifications

- Powder coated aluminum construction
- Unique ribbed 60mm high handrail profile
- No-weld modular assembly
- No hot work required to customise
- 50x50mm square post uprights

- Posts have 4 anchors for superior stability
- E Fully modular system 4 different configurations available
- Swing and sliding gates available
- Mezzanine floor options with kickplate available





Kitset Bays	Length	Туре	Image
PS1A12SB-P	1200mm	Starter Bay	
PS1A24SB-P	2400mm	Starter Bay	
PS1A12AB-P	1200mm	Add-On Bay	
PS1A24AB-P	2400mm	Add-On Bay	

Detailed Specifications

Application	Pedestrian physical segregation, walkways and safe zones.		
Impact	PedSafe is not recommended for vehicle impact.		
Post Material	Aluminium - 3mm wall thickness		
Rail Material	Aluminium - 2mm wall thickness, gusseted		
Connector	Glass reinforced nylon		
Finish	Powder coated to AS/NZS 3715 - Dulux Powder Coat		
Anchors	Concrete screw bolt anchors - M10 x 60mm		
Post Size	50x50mm SHS		
Rail Size	48W x 60H (mm)		
Base Plate	150x150mm square, 5mm thick, 4x anchor holes 13mm Ø		

Exploded Parts View

